

519,168

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 January 2004 (08.01.2004)

PCT

(10) International Publication Number
WO 2004/002808 A1

(51) International Patent Classification⁷: **B62D 21/02**

Worcestershire B97 5HR (GB). **TROWTON, John, Paul** [GB/GB]; 3 Binswood Street, Leamington Spa, Warwickshire CV32 5RW (GB).

(21) International Application Number:
PCT/GB2003/002603

(22) International Filing Date: 16 June 2003 (16.06.2003)

(74) Agents: **FARROW, Robert, Michael** et al.; Land Rover, Patent Department 53G16/4, Banbury Road, Lighthorne, Warwick CV35 0RG (GB).

(25) Filing Language: English

(81) Designated State (*national*): US.

(26) Publication Language: English

(84) Designated States (*regional*): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(30) Priority Data:
0214773.4 26 June 2002 (26.06.2002) GB

Declaration under Rule 4.17:
— of inventorship (Rule 4.17(iv)) for US only

(71) Applicant (*for all designated States except US*): **FORD GLOBAL TECHNOLOGIES, LLC** [US/US]; Suite 600, Parklane Towers East, One Parklane Boulevard, Dearborn, MI 48126-2490 (US).


Published:
— with international search report

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **JENNINGS, Vincent** [GB/GB]; 3 Mansell Road, Crabbs Cross, Redditch,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: VEHICLE CHASSIS



(57) Abstract: A vehicle chassis comprises two longitudinal side rails (10, 12). A first cross member (14) extends in a transverse direction between the front ends of the side rails (10, 12) and a second cross member (20) extends in a transverse direction between the central portions of the side rails. The chassis further comprises two secondary longitudinal members (22, 24) extending between the first cross member (14) and the second cross member (20), and the secondary longitudinal members are each connected to the side rails by means of a central support section (28, 30) which is longitudinally spaced between the first and second cross members (14, 20). The structure provides rigid support for the vehicle suspension and for a eye recovery (42), and crumples in a controlled way on frontal impact.

WO 2004/002808 A1